



The shape of the first two sizes is adapted to the shape of the pipeline, while the larger sizes are pillow-shaped to simplify insertion through the manholes. Plugs are available in seven standard sizes, both sealing and bypass types.



Fit all standard egg-shaped pipes

Two design versions

Wide range

EI DESIGN (FOR SMALL SIZES)



PLUGY EI 2
503406

Front



Back

EI PILLOW DESIGN (FOR LARGER SIZES)



PLUGSY EI 3 PILLOW
526695



Deflated pillow plugsy EI



NOTE: Pillow EI plug should be placed vertically



GEKA (EI PILLOW)

EGG-SHAPED PLUGS – PLUGY EI, PLUGY EI PILLOW AND PLUGSY EI, PLUGSY EI PILLOW

1. 12.

ACCESSORIES EI DESIGN



SINGLE FITTING CONTROLLER, 0.9 KG
1.5 BAR
74609



INFLATION HOSE, 10 M, RED, 1.2 KG
74268



INFLATION HOSE, 10 M, BLUE, 1.2 KG
71248



INFLATION HOSE, 10 M, YELLOW, 1.2 KG
76686



POLY LIFT INFLATION HOSE, 5 M, 1.9 KG
60957



POLY LIFT INFLATION HOSE, 10 M, 2.4 KG
60958

ACCESSORIES EI PILLOW DESIGN



DOUBLE FITTING CONTROLLER, 2.0 KG
504061



INFLATION HOSE 10 M WITH SAFETY GEKA COUPLING, 3.0 KG
519817

PLUGY EI - BLOCKING PLUGS

PART NUMBER	NOMINAL SIZE	SIZE USAGE RANGE		REQUIRED INFLATION PRESSURE (BAR)	MAX. ALLOWED BACK PRESSURE		DEFLATED PLUG			PRODUCT WEIGHT (KG)	EYE BOLT M THREAD	SHACKLE M THREAD	INFLATION VALVE THREAD SIZE
		MIN. DIA. (MM)	MAX. DIA. (MM)		WATER HEAD (BAR)	WATER HEAD (M)	DIAMETER (MM)	WIDTH (MM)	LENGTH (MM)				
503485	EI 1	200/300	250/375	1.5	0.5	5	180x265	/	600	7	8	NA	TYPE 26
503486	EI 2	300/450	350/525	1.5	0.5	5	280x415	/	700	14.8	8	NA	TYPE 26
526694	EI 3 - PILLOW	400/600	500/750	1.3	0.5	5	420	660	1800	20.1	NA	12 x 2	2 x R1/2"
568807	EI 3s - PILLOW	600/900	600/900	1.3	0.5	5	636	1000	1800	26.7	NA	12 x 2	2 x R1/2"
519444	EI 4 - PILLOW	700/1050	800/1200	0.9	0.5	5	751	1180	2300	36.1	NA	12 x 2	2 x R1/2"
519447	EI 5 - PILLOW	900/1350	1000/1500	0.8	0.5	5	955	1500	2900	53.9	NA	12 x 3	2 x R1/2"
536345	EI 6 - PILLOW	1200/1800	1400/2100	0.6	0.4	4	1394	2190	3400	92.4	NA	12 x 3	2 x R1/2"

PLUGSY EI - BYPASS PLUGS

PART NUMBER	NOMINAL SIZE	SIZE USAGE RANGE		REQUIRED INFLATION PRESSURE (BAR)	MAX. ALLOWED BACK PRESSURE		DEFLATED PLUG			PRODUCT WEIGHT (KG)	EYE BOLT M THREAD	SHACKLE M THREAD	BYPASS DIAMETER
		MIN. DIA. (MM)	MAX. DIA. (MM)		WATER HEAD (BAR)	WATER HEAD (M)	DIAMETER (MM)	WIDTH (MM)	LENGTH (MM)				
504158	EI 1	200/300	250/375	1.5	0.5	5	180x265	/	600	10.2	8	NA	2"
504160	EI 2	300/450	350/525	1.5	0.5	5	280x415	/	700	17.9	8	NA	3"
526695	EI 3 - PILLOW	400/600	500/750	1.3	0.5	5	420	660	1800	25.4	NA	12 x 2	2"
568808	EI 3s - PILLOW	600/900	600/900	1.3	0.5	5	636	1000	1800	32.1	NA	12 x 2	2"
519448	EI 4 - PILLOW	700/1050	800/1200	0.9	0.5	5	751	1180	2300	42.1	NA	12 x 2	2"
519449	EI 5 - PILLOW	900/1350	1000/1500	0.8	0.5	5	955	1500	2900	60.8	NA	12 x 3	2"
536350	EI 6 - PILLOW	1200/1800	1400/2100	0.6	0.4	4	1394	2190	3400	100.9	NA	12 x 3	2"